

Model 52-1W Personnel Gamma Portal Monitor



Ludlum Measurements, Inc.

Features

- Easy Setup, Operation, and Transportation
- Four Plastic Scintillator Side Detectors
- Angled Display for Ease of Use
- Detector LEDs Indicate Alarm Location
- 61 cm (24 in.) Wide Opening
- Meets FEMA-REP-21 Standards
- Flexible Power Options
- Water-Resistant



Introduction

The Model 52-1W Portal Monitor is the water-resistant version of the Model 52-1 Portal Monitor, used for gamma contamination monitoring of personnel. It assembles and disassembles quickly and easily without tools, and is packed in a wheeled, lockable transport/storage case for rapid deployment.

The portal monitor may be operated on a walk-through basis. Non-volatile parameters are factory preset in accordance with the FEMA standard. Electronics are microprocessor-based for reliability. Daylight-visible LEDs indicate count-cycle status, while loud audible signals that feature user-adjustable volume and on/off function provide additional indicators for the operator. The Model 52-1 features flexible options for powering the device making it a versatile and portable for many situations. See details below.

Specifications

Part Number: 48-4300

SENSITIVITY: This instrument will detect the gamma emissions from a 1.0 μCi source when it is located at mid-frame of the portal monitor in a 10 $\mu\text{R/hr}$ background (per the suggested standard in FEMA report "Contamination Monitoring Standard for a Portal Monitor Used for Emergency Response," Sept. 1992)

DISPLAY: two-line x 20-character LCD shows background rates from all detectors and sigma values above background, daylight-visible LEDs show instrument status and radiation alarm location

COUNT TIME: adjustable from 0 to 20 seconds, with "0" second setting for walk-through mode

LED COLOR INDICATORS

- **ENTER/CHECKING:** green; indicates system is ready for use, flashing LED indicates count is in progress
- **INCOMPLETE/UPDATING:** amber; indicates user has vacated the portal before counting was completed or that an update is in progress
- **ALARM:** red LED and user-adjustable audible signal (greater than 60 dB at 61 cm [24 in.]
- **FAILURE:** red; indicates a high or low background

INFRARED SENSOR: senses portal occupancy

PARAMETERS: all parameters are stored in non-volatile memory

DETECTORS: 4 each 2.75 L (168 in³) plastic scintillators; total 11 L (672 in³)

OUTPUT: RS-232 and relay output connectors located on the bottom of the electronics chassis

TEMPERATURE RANGE: -20 to 50 °C (-4 to 122 °F)

ENVIRONMENTAL RATING: IP rating of 53

CONSTRUCTION: aluminum housing with beige powder-coat

PORTAL OVERALL DIMENSIONS: 211 x 81.3 x 45 cm (83 x 32 x 17.5 in.) (H x W x D)

PORTAL INSIDE DIMENSIONS: 206 x 61 cm (81 x 24 in.) (H x W)

WEIGHT: approximately 32 kg (70 lb), with case 45 kg (100 lb)

POWER OPTIONS

- 85 to 250 Vac 50/60 Hz using supplied power supply (12 Vdc wall adapter)
- Supplied 12 Vdc cigarette lighter adapter cable
- 3 or 6 "D" cell batteries. Battery life: typically 69 hours for six batteries or 28 hours for three batteries

TRANSPORT/STORAGE CASE DIMENSIONS (Included): 122 x 61 x 30.5 cm (48 x 24 x 12 in.) (H x W x D)

OPTIONAL VEHICLE MONITOR CONVERSION KIT FOR MODEL 52-1 SERIES: enables the user to reconfigure the Model 52-1 Series of portal monitors as a vehicle monitor. Includes stands and cable. Monitor available separately. Part Number 4215-1099



Right: Shown configured as vehicle monitor using optional conversion kit P/N 4215-1099

Ludlum Measurements, Inc. P.O. Box 810, Sweetwater, Texas 79556

Web: <http://www.ludlums.com> Tel: 800-622-0828 / 325-235-5494 / Fax: 325-235-4672 / Email: sales@ludlums.com

Note: specifications subject to change without notification. We are not responsible for errors or omissions.

March 2018