



INSPECTION CERTIFICATE

IPCE - 299 - Rev 2

Product : FLUXO P172- Red Dye Penetrant - Aerosol

BATCH : L211025

Manufacture Date : 25/10/21

Use Before : 21/10/26

We hereby certify that the above product **FLUXO P172** meets the requirements of the following specifications :

- EN ISO 3452-2 - Type 2 - Sensitivity Level 2 - Method A/C
- EN ISO 3452-6
- ASTM E1417 Paragraph 5.1 - ASTM E165 Paragraph 7.1
- ASME Boiler & Pressure Vessel Code - Section V - Article 6 - Paragraph T-641
- Low in Sulphur & Halogens (< 200ppm)
- Was manufactured in accordance with our standard procedures (requirement ISO 9001 for Quality System)
- BIODEGRADABILITY : FLUXO P172 is a BIODEGRADABLE Penetrant

The following results were obtained :

Characteristic	Test Method	Requirement	Results
Appearance & Colour	EN ISO 3452-2 § 6.1	Red Liquid	Conform
Sensitivity	EN ISO 3452-2 § 6.2	Level 2	Level 2
Density (20°C)	EN ISO 3452-2 § 6.3	0,885 to 0,925 g/mL	0.895 g/mL
Viscosity (40°C)	EN ISO 3452-2 § 6.4	5,75 to 7,05 mm ² .s ⁻¹	6.64 mm ² .s ⁻¹
Washability	EN ISO 3452-2 § 6.6	Equal to Standard	Conform
Chlorine + Fluorine + Bromure	EN ISO 3452-2 § 6.12	< 200 ppm	< 200 ppm
Sulfur	EN ISO 3452-2 § 6.12	< 200 ppm	< 200 ppm

Jocelyne BONHAURE
Laboratory Technician

- The batch number appears on the label of bulk containers. Aerosols Cans have batch numbers printed on bottom of the can.
- The results are obtained at the time of manufacture. Age and use may alter the properties of the product.