

ASTM Thermometers, Mercury, Fahrenheit

Part Number & Name:



H-2600.1F

General Use, 0 to 302°F, Subdiv. 2.0°F, Length 12.5" (322mm), Immersion 3" (76mm) Mercury Thermometer

H-2600.2F

General Use, 20 to 580°F, Subdiv. 2.0°F, Length 15.325" (390mm), Immersion 3" (76mm) Mercury Thermometer

H-2600.3F

General Use, 20 to 760°F, Subdiv. 2.0°F, Length 16.25" (413mm), Immersion 3" (76mm) Mercury Thermometer

H-2600.5F

Cloud and Pour, -36 to 120°F, Subdiv. 2.0°F, Length 9.125" (231mm), Immersion 4.26" (108mm) Mercury Thermometer

H-2600.6F

Low Cloud and Pour, -112 to 70°F, Subdiv. 2.0°F, Length 9.125" (231mm), Immersion 3" (76mm)

H-2600.7F

Low Distillation, 30 to 580°F, Subdiv. 2.0°F, Length 15.25" (386mm), Immersion Total Mercury Thermometer

H-2600.8F

High Distillation, 30 to 760°F, Subdiv. 2.0°F, Length 15.25" (386mm), Immersion Total Mercury Thermometer

H-2600.9F

Pesky-Martens Low, 20 to 230°F, Subdiv. 1.0°F, Length 11.25" (287mm), Immersion 2.25" (57mm) Mercury Thermometer

H-2600.10F

Pesky-Martens High, 200 to 700°F, Subdiv. 5.0°F, Length 11.25" (287mm), Immersion 2.25" (57mm) Mercury Thermometer

H-2600.11F

Cleveland Open Flash, 20 to 760°F, Subdiv. 5.0°F, Length 12.125" (308mm), Immersion 1" (25mm) Mercury Thermometer

H-2600.12F

Gravity, -5 to 215°F, Subdiv. 0.5°F, Length 16.5" (420mm), Immersion Total Mercury Thermometer

H-2600.15F

Low Softening Point, 30 to 180°F, Subdiv. 0.5°F, Length 15.625" (397mm), Immersion Total Mercury Thermometer

H-2600.16F

High Softening Point, 85 to 392°F, Subdiv. 1.0°F, Length 15.625" (397mm), Immersion Total Mercury Thermometer

H-2600.17F

Saybolt Viscosity, 66 to 80°F, Subdiv. 0.2°F, Length 10.875" (275mm), Immersion Total Mercury Thermometer

H-2600.18F

Saybolt Viscosity, 94 to 108°F, Subdiv. 0.2°F, Length 10.875" (275mm), Immersion Total Mercury Thermometer

H-2600.19F

Saybolt Viscosity, 120 to 134°F, Subdiv. 0.2°F, Length 10.875" (275mm), Immersion Total Mercury Thermometer

H-2600.20F

Saybolt Viscosity, 134 to 148°F, Subdiv. 0.2°F, Length 10.875" (275mm), Immersion Total Mercury Thermometer

H-2600.22F

Saybolt Viscosity, 204 to 218°F, Subdiv. 0.2°F, Length 0.875" (275mm), Immersion Total Mercury Thermometer

H-2600.28F

Kinematic Viscosity, 97.5 to 102.5°F, Subdiv. 0.1°F, Length 12" (305mm), Immersion Total Mercury Thermometer

H-2600.33F

Aniline Point, -36.5 to 107.5°F, Subdiv. 0.5°F, Length 16.5" (419mm), Immersion 2" (50mm) Mercury Thermometer

H-2600.35F

Aniline Point, 194 to 338°F, Subdiv. 0.5°F, Length 16.5" (419mm), Immersion 2" (50mm) Mercury Thermometer

H-2600.45F

Kinematic Viscosity, 74.5 to 79.5°F, Subdiv. 0.1°F, Length 12" (305mm), Immersion Total Mercury Thermometer

H-2600.47F

Kinematic Viscosity, 137.5 to 142.5°F, Subdiv. 0.1°F, Length 12" (305mm), Immersion Total Mercury Thermometer

H-2600.57F

Tag Closed Tester, Low Range, -4 to 122°F, Subdiv. 1.0°F, Length 15" (379mm), Immersion Total Mercury Thermometer

H-2600.63F

Precision, 18 to 89°F, Subdiv. .2°F, Length 15" (279mm), Immersion Total Mercury Thermometer

H-2600.64F

Precision, 77 to 131°F, Subdiv. .2°F, Length 15" (379mm), Immersion Total Mercury Thermometer

H-2600.110F

Kinematic Viscosity, 272.5 to 277.5°F, Subdiv. .1°F, Length 12" (305mm), Immersion Total Mercury Thermometer

H-2600.113F

Bituminous Softening Point, 30 to 350°F, Subdiv. 1.0°F, Length 16" (406mm), Immersion Total Mercury Thermometer

CAUTION: These thermometers contain mercury. There are restrictions on their sale and shipment. Please check laws in your area or contact us before ordering. Mercury Thermometers require ground shipment in the U.S. and ship as Dangerous Goods.

Standards ASTM D113 ASTM D2500 ASTM D97 ASTM D1856 ASTM D402 ASTM D1310 ASTM D3143 ASTM D4867 ASTM D6925
ASTM D2041 ASTM D139 ASTM D36 ASTM D1200 ASTM D333 ASTM D365 ASTM D5 ASTM D88 ASTM D244 ASTM D6927 ASTM
D2170 ASTM D2171 ASTM D6084 ASTM D1321