

EchoTherm™

High Temperature Ultrasonic Couplant

EchoTherm is a high temperature thickness gauging and corrosion testing couplant that has an operating range of -40° to 1250°F (-40° to 675°C) and an auto-ignition temperature of 1300°F (704°C).

PRODUCT DESCRIPTION

EchoTherm removes the industrial accident liability, personnel risk and “startle factor” of surprise auto-ignition events when performing high temperature thickness gaging or corrosion profiling.

Due to the small mass of EchoTherm used for ultrasonic thickness gaging, the slow rate of thermal decomposition and local ventilation, the smoke is not anticipated to be a health hazard.

Residue: EchoTherm will leave a charred polymer residue that must be removed for subsequent inspections. If no residue is preferred, EchoTherm Extreme is recommended.

EchoTherm contains a polymer which melts (and begins to smoke) at 750°F (400°C) which extends the operating range, however, it is not necessary to reach this temperature to obtain instant readings. EchoTherm is the most economical ultra-high temperature couplant.

If you are testing below 700°F, **VersaSonic** is the recommended couplant with an operating range of -10° to 700°F. If you are testing below 850°F, **HiTempco+** is the ideal couplant with no residue and an operating range of -50° to 850°F.



PRODUCT SPECIFICATIONS

Operating Range:

-40° to 1250°F (-40° to 675°C)

■ Auto-ignition Temperature*: 1300°F (704°C)

*Test by John A Kennedy & Assoc., ASTM E659-14

■ Viscosity: Thick Paste

PACKAGING

ETM-02:

2 fluid oz. / 4 oz. avdp (weight), metal tubes

SDS available at: echoultrasonics.com



Echo Ultrasonics®, LLC
774 Marine Drive | Bellingham, WA 98225
echoultrasonics.com | sales@echoultrasonics.com
360.671.9121